



JABATAN AIR NEGERI SABAH

Butiran Pendaftaran

No Sijil : JANS.2025.16e

Nama Pembekal : **CEMERLANG PADAS SDN BHD**
Lot 32, 2nd Floor, Block F, KK Times Square, Off Coastal Road,
88100 Kota Kinabalu, Sabah

Nama Pembuat /
Pengilang : **GEORGE KENT (MALAYSIA) BERHAD**
1115, Jalan Puchong, Taman Meranti Jaya,
47120 Puchong, Selangor

Nama Prinsipal /
Pemilik : **GEORGE KENT (MALAYSIA) BERHAD**
1115, Jalan Puchong, Taman Meranti Jaya,
47120 Puchong, Selangor

Nama Produk : Meter

Kategori : A [Measuring Device]

Kelas/Saiz/Model : (Sila rujuk Jadual di muka surat belakang)

Jenama : **GKM**

Piawaian : ISO 4046-1:2014, ISO 4046-4:2014

Tarikh dikeluarkan : 20 Februari 2025

Sah sehingga : 20 Februari 2027

Perihal produk :

NAMA PRODUK	MODEL	SIRI	PERIHAL/KELAS/SAIZ
CUSTODY TRANSFER METER - MECHANICAL METER	GKMV30; VOLUMETRIC WATER METER	NA/PERMANENT FLOWRATE (Q3): 6.3 M3/H; MEASURING RANGE (Q3/Q1): R160; MAXIMUM ADMISSIBLE (MAP) 16 BAR; TEMPERATURE CLASS: T50; PRESSURE LOSS: LESS THAN 0.63 BAR	ACCURACY CLASS 2: ANALOGUE METER; CHARACTERISTICS: IN-LINE METERS; ORIENTATION: ANY POSITION; BODY MATERIAL: BRASS, GRADE CW617N; END CONNECTION: THREADED END/NOMINAL SIZE: DN25; LENGTH: 200MM/TYPE: ANALOGUE METER NOMINAL SIZE: DN25; LENGTH 200MM
	GKMV30; VOLUMETRIC WATER METER	NA/PERMANENT FLOWRATE (Q3): 16.0 M3/H; MEASURING RANGE (Q3/Q1): R160; MAXIMUM ADMISSIBLE (MAP) 16 BAR; TEMPERATURE CLASS: T50; PRESSURE LOSS: LESS THAN 0.63 BAR	ACCURACY CLASS 2: ANALOGUE METER; CHARACTERISTICS: IN-LINE METERS; ORIENTATION: ANY POSITION; BODY MATERIAL: BRASS, GRADE CW617N; END CONNECTION: THREADED END/NOMINAL SIZE: DN40; LENGTH: 300MM/TYPE: ANALOGUE METER NOMINAL SIZE: DN40; LENGTH 300MM

No Sijil : JANS.2025.16e
 Perihal :

	GKMV30; VOLUMETRIC WATER METER	NA/PERMANENT FLOWRATE (Q3): 2.5 M3/H; MEASURING RANGE (Q3/Q1): R160; MAXIMUM ADMISSIBLE (MAP) 16 BAR; TEMPERATURE CLASS: T50; PRESSURE LOSS: LESS THAN 0.63 BAR	ACCURACY CLASS 2; ANALOGUE METER; CHARACTERISTICS: IN-LINE METERS; ORIENTATION: ANY POSITION; BODY MATERIAL: PLASTIC, GRADE POLYOXYMETHYLENE (POM); END CONNECTION: THREADED END/NOMINAL SIZE: DN15; LENGTH: 115MM AND 165MM/TYPE: ANALOGUE METER NOMINAL SIZE: DN15; LENGTH: 115MM AND 165MM
	GKMW200; WOLTMANN WATER METER	NA/PERMANENT FLOWRATE (Q3): 63 M3/H; MEASURING RANGE (Q3/Q1): R125; MAXIMUM ADMISSIBLE (MAP) 16 BAR; TEMPERATURE CLASS: T50; PRESSURE LOSS: LESS THAN 0.25 BAR	ACCURACY CLASS 2; ANALOGUE METER; ORIENTATION: ANY POSITION; CHARACTERISTICS: IN- LINE METERS; BODY MATERIAL: DUCTILE IRON; END CONNECTION: FLANGED END/NOMINAL SIZE: DN50; LENGTH: 200MM/TYPE: ANALOGUE METER NOMINAL SIZE: DN50; LENGTH 200MM
	GKMW200; WOLTMANN WATER METER	NA/PERMANENT FLOWRATE (Q3): 160 M3/H; MEASURING RANGE (Q3/Q1): R125; MAXIMUM ADMISSIBLE (MAP) 16 BAR; TEMPERATURE CLASS: T50; PRESSURE LOSS: LESS THAN 0.25 BAR	ACCURACY CLASS 2; ANALOGUE METER; ORIENTATION: ANY POSITION; CHARACTERISTICS: IN- LINE METERS; BODY MATERIAL: DUCTILE IRON; END CONNECTION: FLANGED END/NOMINAL SIZE :DN80, LENGTH: 200MM/TYPE: ANALOGUE METER NOMINAL SIZE: DN80; LENGTH: 200MM

FOR WEBSITE