



## JABATAN AIR SABAH

### Butiran Pendaftaran

No Sijil : **JANS.2026.07 (a)**

Nama Pembekal : **ECO VALVES & FITTINGS SDN BHD**  
8, Persiaran Perusahaan Kledang Utara 1/4, Taman Perindustrian Chandan Raya,  
Menglembu, 31450 Ipoh, Perak Darul Ridzuan

Nama Pengilang : **ECO VALVES & FITTINGS SDN BHD**  
8, Persiaran Perusahaan Kledang Utara 1/4, Taman Perindustrian Chandan Raya,  
Menglembu, 31450 Ipoh, Perak Darul Ridzuan

Nama Prinsipal / Pemilik : **ECO VALVES & FITTINGS SDN BHD**  
8, Persiaran Perusahaan Kledang Utara 1/4, Taman Perindustrian Chandan Raya,  
Menglembu, 31450 Ipoh, Perak Darul Ridzuan

Nama Produk : Fittings

Kategori : A - [Conveyance of Water]

Kelas/Saiz/Model : (Sila rujuk Jadual di muka surat belakang)

Jenama : **EVF**

Piawaian : MS 1919:2013, SPESIFIKASI JKR 20200-0048-99,  
SPESIFIKASI JKR 20200-0042-99

Tarikh Dikeluarkan : 21 Januari 2026

Sah Sehingga : 21 Januari 2028

Perihal Produk :

<b>NAMA PRODUK</b>	<b>MODEL</b>	<b>SIRI</b>	<b>PERIHAL/CLASS/SAIZ</b>
FITTINGS	DOUBLE FLANGED 90 DEG AND 90 DEG DUCKFOOT BENDS	NA/NA	D.I. FITTINGS/80, 100, 125, 150, 200, 250, 300, 350, 400, 450, 500, 600/ NOMINAL PRESSURE: PN 16 EXTERNAL COATING: BITUMINOUS OR EPOXY (COLD APPLIED OF FUSION BONDED) INTERNAL LINING: CEMENT MORTAR OR EPOXY (COLD APPLIED OR FUSION BONDED)
	BLANK FLANGES	NA/NA	D.I. FITTINGS/ 80, 100, 125, 150, 200, 250, 300, 350, 400, 450, 500, 600/NOMINAL PRESSURE : PN 16 EXTERNAL COATING: BITUMINOUS OR EPOXY (COLD APPLIED OR FUSION BONDED) INTERNAL LINING: CEMENT MORTAR OR EPOXY (COLD APPLIED OR FUSION BONDED)

No Sijil : JANS.2026.07 (a)

Perihal :

			D. I. FITTINGS/ 80 X 80, 100 X 80, 100 X 100, 125 X 80, 125 X 100, 125 X 125, 150 X 80, 150 X 100, 150 X 125, 150 X 150, 200 X 80, 200 X 100, 200 X 125, 200 X 150, 200 X 200, 250 X 80, 250 X 100, 250 X 150, 250X 200, 250 X 250, 300 X 80, 300 X 100, 300 X 150, 200 X 200, 300 X 250, 300 X 300, 350 X 80, 350 X 100, 350 X 150, 350 X 200, 350, 250, 350 X 350, 400 X 80, 400 X 100, 400 X 150, 400 X 200, 400 X 250, 400 X 300, 400 X 400, 450 X 100, 450 X 150, 450 X 200, 450 X 250, 450 X 300, 450 X 400, 450 X 450, 500 X 100, 500 X 200, 500 X 400, 500 X 500, 600 X 200, 600 X 400, 600 X 600/ NOMINAL PRESSURE: PN 16 EXTERNAL COATING: BITUMINOUS OR EPOXY (COLD APPLIED OR FUSION BONDED) INTERNAL LINING: CEMENT MORTAR OR EPOXY (COLD APPLIED OR FUSION BONDED)
	ALL FLANGED TEES	NA/NA	
	DOUBLE FLANGED TAPERS	NA/NA	D.I. FITTINGS/ 100 X 80, 125 X 100, 150 X 125, 200 X 150, 250 X 200, 300 X 250, 350 X 300, 400 X 300, 400 X 350, 450 X 400, 500 X 400, 600 X 500 / NOMINAL PRESSURE: PN 16 EXTERNAL COATING: BITUMINOUS OR EPOXY (COLD APPLIED OR FUSION BONDED) INTERNAL LINING: CEMENT MORTAR OR EPOXY (COLD APPLIED OF FUSION BONDED)
	REDUCING FLANGES	NA/NA	D.I. FITTINGS/ 200X80, 200X100, 200 X 125, 350 X 250, 400 X 250, 400 X 300,/ NOMINAL PRESSURE: PN16 EXTERNAL COATING: BITUMINOUS OR EPOXY (COLD APPLIED OR FUSION BONDED) INTERNAL LINING: CEMENT MORTAR OR EPOXY (COLD APPLIED OF FUSION BONDED)