



JABATAN AIR SABAH

Butiran Pendaftaran

No Sijil : **JANS.2026.65**

Nama Pembekal : **KAIZEN MARKETING SDN BHD**
31A, Jalan Pinggir, Off Jalan Ipoh,
51200 Kuala Lumpur

Nama Pengilang : **TAIZHOU GREEN VALVES**
No.110 Donghai Road, Baiyan Industrial Yuhuan County, Taizhou City,
317600 Taizhou, Zhejiang, China

Nama Prinsipal /
Pemilik : **N ENTERPRISE AND TRADING**
31A, Jalan Pinggir, Off Jalan Ipoh,
51200 Kuala Lumpur

Nama Produk : Copper And Copper Alloys Plumbing Fittings

Kategori : A - Conveyance Of Water

Kelas/Saiz/Model : (Sila rujuk Jadual di muka surat belakang)

Jenama : **N**

Piawaian : BS EN 1254-3: 2021

Tarikh Dikeluarkan : 12 Ogos 2026

Sah Sehingga : 12 Ogos 2028

Perihal Produk :

NAMA PRODUK	MODEL	SIRI	PERIHAL/CLASS/SAIZ
COPPER AND COPPER ALLOYS PLUMBING FITTINGS	ELBOW	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN16, DN20, DN25 & DN32
	FEMALE ELBOW	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN16 x 1/2", DN20 x 1/2", DN20 x 3/4", DN25 x 3/4", DN25 x 1", DN32 x 3/4" & DN32 x 1"
	FEMALE SOCKET	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN16 x 1/2", DN20 x 1/2", DN20 x 3/4", DN25 x 3/4", DN25 x 1", DN32 x 3/4" & DN32 x 1"
	MALE ELBOW	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES" NOMINAL SIZE: DN16 x 1/2", DN20 x 1/2", DN20 x 3/4", DN25 x 3/4", DN25 x 1", DN32 x 3/4" & DN32 x 1"
	MALE SOCKET	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES" NOMINAL SIZE: DN16 x 1/2", DN20 x 1/2", DN20 x 3/4", DN25 x 1/2", DN25 x 3/4", DN25 x 1", DN32 x 3/4" & DN32 x 1"
	REDUCING SOCKET	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN20 x DN16, DN25 x DN16, DN25 x DN20 & DN32 x DN25
	REDUCING TEE	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN20 x DN16 x DN20, DN25 x DN16 x DN25 & DN25 x DN20 x DN25
	SOCKET	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN16, DN20, DN25 & DN32
	TEE	TYPE A; WITH ABUTMENT	MATERIAL GRADE CW617N; DEZINCFICATION RESISTANCE = GRADE B; FOR USE WITH PE-X PIPES NOMINAL SIZE: DN16, DN20, DN25 & DN32